

S5-GR1P(7-10)K

Solis Single Phase Inverters



Features:

- ▶ Max. efficiency 98.1%
- ▶ Max. input current **14A**
- ▶ Complies with all state network requirements
- ▶ Integrate with adjustable Volt-Watt and Volt-Var function
- ▶ DRM integrated, fully comply with AS/NZS 4777.2:2020
- ▶ Built-in DC-PV2 Switch (optional), comply with AS/NZS 5033 requirements
- ▶ Support 24h consumption monitoring with a smart meter
- ▶ Super high frequency switching technology
- ▶ 3 MPPT design with precise MPPT algorithm
- ▶ Integrated Export Power Manager(EPM)
- ▶ Compact and lightweight
- ▶ Voltage active power and reactive power



Model:

- | | |
|-----------|------------|
| S5-GR1P7K | S5-GR1P8K |
| S5-GR1P9K | S5-GR1P10K |

Datasheet

Model Name	S5-GR1P7K	S5-GR1P8K	S5-GR1P9K	S5-GR1P10K
Input DC				
Recommended max. PV power	9.1 kW	10.4 kW	11.7 kW	13 kW
Max. input voltage		600V		
Rated voltage		330V		
Start-up voltage		120V		
MPPT voltage range		100-500V		
Max. input current		14 A / 14 A / 14 A		
Max. short circuit current		22 A / 22 A / 22 A		
MPPT number/Max. input strings number		3/3		
Output AC				
Rated output power	7 kW	8 kW	9 kW	10 kW
Rated apparent output power	7 kVA	8 kVA	9 kVA	10 kVA
Max. apparent output power	7 kVA	8 kVA	9 kVA	10 kVA
Max. output power	7 kW	8 kW	9 kW	10 kW
Rated grid voltage		1/N/PE, 230 V		
Rated grid frequency		50 Hz		
Rated grid output current	30.4 A	34.8 A	39.1 A	43.5 A
Max. output current	33.7 A	36.6 A	41.3 A	45.9 A
Power Factor		>0.99 (0.8 leading - 0.8 lagging)		
THDi		<3%		
Efficiency				
Max. efficiency		98.1%		
EU efficiency		97.3%		
Protection				
DC reverse-polarity protection		Yes		
Short circuit protection		Yes		
Output over current protection		Yes		
Surge protection		Yes		
Grid monitoring		Yes		
Anti-islanding protection		Yes		
Temperature protection		Yes		
Integrated DC switch		Optional (PV2 Switch)		
General Data				
Dimensions (W*H*D)		333*573*249 mm		
Weight		18 kg		
Topology		Transformerless		
Self consumption (night)		<1 W		
Operating ambient temperature range		-25 ~ +60°C		
Relative humidity		0-100%		
Ingress protection		IP65		
Cooling concept		Natural convection		
Max. operation altitude		2000 m		
Grid connection standard	AS/NZS 4777.2:2020, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530			
Safety/EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-1/-2/-3/-4			
Features				
DC connection		MC4 connector		
AC connection		Quick connection plug		
Display		LCD		
Communication		RS485, Optional: Wi-Fi, GPRS		
Country of manufacture		China		